

In the Claims:

Please amend claims 1, 6, 7 and 27-38 as indicated below.

1. (Currently amended) A thread-safe scheduler system, comprising:

a primary scheduler which is executable to schedule requests for networked data resources; and

a secondary scheduler, wherein the secondary scheduler is executable to receive a plurality of requests from a multi-threaded application in a thread-safe manner and send the requests received from the multi-threaded application to the primary scheduler in a thread-safe manner.

2. (Original) The system of claim 1, wherein the primary scheduler is single-threaded.

3. (Original) The system of claim 1, wherein the secondary scheduler is multi-threaded.

4. (Original) The system of claim 1, wherein the secondary scheduler is executable to receive the plurality of requests from the multi-threaded application through a lock in a thread-safe manner.

5. (Original) The system of claim 1, wherein the primary scheduler is executable to receive the plurality of requests from the secondary scheduler through a lock in a thread-safe manner.

6. (Currently amended) The system of claim 1, wherein the resources comprise a management information server, wherein the requests received from the multi-threaded application comprise management requests, and wherein the multi-threaded application

comprises a multi-threaded manager application.

7. (Currently amended) The system of claim 1, further comprising:

a management information server coupled to the primary scheduler through a management interface, wherein the primary scheduler is operable to send the requests from the secondary scheduler to one or more managed objects through the management information server.

8. (Original) The system of claim 7, wherein the managed objects comprise one or more objects corresponding to a telephone network.

9. (Original) The system of claim 7, wherein the managed objects comprise an object corresponding to a telecommunications device.

10. (Original) The system of claim 7, wherein the management interface comprises Portable Management Interface (PMI), wherein PMI is single-threaded, and wherein PMI comprises a plurality of functions which are operable to carry out the requests.

11. (Original) The system of claim 10, wherein the requests comprise callback functions, and wherein the callback functions are executable to send responses to the requests to the multi-threaded application.

12. (Original) The system of claim 1, wherein the primary scheduler comprises a primary queue which is operable to hold pending requests and responses to the requests.

13. (Original) The system of claim 1, wherein the secondary scheduler comprises a secondary queue which is operable to hold pending requests.

14. (Original) The system of claim 1, further comprising:

a communication pipe between the primary scheduler and secondary scheduler, wherein the secondary scheduler uses the communication pipe to wake the primary scheduler prior to sending one of the requests to the primary scheduler.

15. (Original) A thread-safe method for using a management interface for management of a plurality of managed objects on a network, the method comprising:

receiving a plurality of management requests from a multi-threaded manager application into a secondary scheduler in a thread-safe manner;

scheduling the plurality of management requests in a secondary queue in the secondary scheduler after receiving the management requests from the manager application;

sending the management requests from the secondary scheduler to a primary scheduler in a thread-safe manner;

scheduling the management requests in a primary queue in the primary scheduler,

executing the management requests on the managed objects after scheduling the management requests in the primary queue.

16. (Original) The method of claim 15, wherein executing the management requests on the managed objects further comprises sending the management requests to a management information server coupled to the managed objects.

17. (Original) The method of claim 15, wherein each of the management requests comprises a corresponding callback function.

18. (Original) The method of claim 17, further comprising:

receiving a response to one of the management requests from one of the managed objects after executing that management requests on one of the managed objects; and

executing the corresponding callback function for that management request to send the response to the multi-threaded manager application.

19. (Original) The method of claim 18, further comprising:

enqueueing the response in the primary queue after receiving the response from one of the managed objects;

finding the callback function corresponding to the response after enqueueing the response; and

dequeueing the response from the primary queue before executing the corresponding callback function to send the response to the multi-threaded manager application.

20. (Original) The method of claim 15, wherein the management interface comprises Portable Management Interface (PMI), wherein PMI is single-threaded, and wherein PMI comprises a plurality of functions which are operable to execute the management requests.

21. (Original) The method of claim 15, wherein the managed objects comprise one or more objects corresponding to a telephone network.

22. (Original) The method of claim 15, wherein the managed objects comprise an object corresponding to a telecommunications device.

23. (Original) The method of claim 15, wherein the receiving the plurality of management requests from the multi-threaded manager application into the secondary scheduler in the thread-safe manner comprises receiving the plurality of management requests through a thread-safe lock.

24. (Original) The method of claim 15, wherein sending the management requests to the primary scheduler in the thread-safe manner comprises dispatching the management requests through a thread-safe lock.

25. (Original) The method of claim 15, wherein the primary scheduler is executed in a single thread associated with the management interface, and wherein the secondary scheduler is executed in at least one different thread.

26. (Original) The method of claim 15, wherein the secondary scheduler is multi-threaded.

27. (Currently amended) A ~~carrier~~ tangible, computer-readable medium comprising program instructions, wherein the program instructions are computer-executable to implement:

receiving a plurality of management requests from a multi-threaded manager application into a secondary scheduler in a thread-safe manner;

scheduling the plurality of management requests in a secondary queue in the secondary scheduler after receiving the management requests from the manager application;

sending the management requests from the secondary scheduler to a primary scheduler in a thread-safe manner;

scheduling the management requests in a primary queue in the primary scheduler,

executing the management requests on the managed objects after scheduling the management requests in the primary queue.

28. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of claim 27, wherein executing the management requests on the managed objects further comprises sending the management requests to a management information server coupled to the managed objects.

29. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of claim 27, wherein each of the management requests comprises a corresponding callback function.

30. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of claim 29, wherein the program instructions are further executable to implement:

receiving a response to one of the management requests from one of the managed objects after executing that management request on one of the managed objects; and

executing the corresponding callback function for that management request to send the response to the multi-threaded manager application.

31. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of claim 30, wherein the program instructions are further executable to implement:

enqueueing the response in the primary queue after receiving the response from one of the managed objects;

finding the callback function corresponding to the response after enqueueing the response; and

dequeueing the response from the primary queue before executing the corresponding callback function to send the response to the multi-threaded manager application.

32. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of claim 27, wherein the management interface comprises Portable Management Interface (PMI), wherein PMI is single-threaded, and wherein PMI comprises a plurality of functions which are operable to execute the management requests.

33. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of claim 27, wherein the managed objects comprise one or more objects corresponding to a telephone network.

34. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of claim 27, wherein the managed objects comprise an object corresponding to a telecommunications device.

35. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of claim 27, wherein the receiving the plurality of management requests from the multi-threaded manager application into the secondary scheduler in the thread-safe manner comprises receiving the plurality of management requests through a thread-safe lock.

36. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of claim 27, wherein sending the management requests to the primary scheduler in the thread-safe manner comprises dispatching the management requests through a thread-safe lock.

37. (Currently amended) The ~~earlier~~ tangible, computer-readable medium of

claim 27, wherein the primary scheduler is executed in a single thread associated with the management interface, and wherein the secondary scheduler is executed in at least one different thread.

38. (Currently amended) The ~~carrier~~ tangible, computer-readable medium of claim 27, wherein the secondary scheduler is multi-threaded.